

Specimen Label

GREEN LAWNGER

Turf Paint and Divot Mix Colourant

Green Lawngr restores the natural green colour to turf during dormant periods. Green Lawngr may also be pre-applied to divot mix sand, giving the mix a natural green colour. Green Lawngr contains no hazardous chemicals, heavy metals, or other inert ingredients known to be harmful to turf.

DIRECTIONS

Before applying Green Lawngr, cut turf to desired height. One gallon (3.78 liters) of Green Lawngr will cover 8,000 -12,000 square feet (743-1115 m²) of turf. Use at a rate of 1-2 gallons (3.78-7.57 ltr.) of spray solution per 1,000 square feet. The area covered will vary with the rate of Green Lawngr used, type and condition of grass being treated, and turf colour desired. Green Lawngr may also be tank mixed with fungicides and herbicides. Check manufacturer's label for appropriate usage rates.

Dormant Application

Dilute one gallon (3.78 liters) of Green Lawngr with 7 to 9 gallons (26-34 liters) of water. For a darker turf colour, reduce the volume of water. Some experimentation may be required with the water to colourant ratio to obtain the exact colour desired. Green Lawngr's colour will last the entire dormant season.

Non-Dormant Application

Dilute one gallon (3.78 liters) with 15 to 20 gallons (56-75 liters) of water or 8 oz. Green Lawngr per 1,000 sq. ft. Again, the application rate depends on the desired colour. For best results on any discoloured area, two applications of a higher dilution are recommended to blend the coloured area in with the surrounding healthy turf.

Divot Mix Sand

Mix 6 ounces (177 ml) of Green Lawngr with the same volume of water. Spray or pour the solution onto 100 lbs (45 kg) of divot mix sand in a cement-type mixer. Mix until coloured. Adjust the colourant to water ratio to achieve the desired colour.

For best results, use low to medium sprayer pressure. Avoid overspray on concrete, masonry, or any other objects where colour is not desired. Permanent staining may occur. Accidental overspray may be removed by a water rinse prior to drying. To prevent rub-off on uniforms, allow Green Lawngr to dry prior to using athletic field. Rinse spray tank, spray nozzles, and screens thoroughly with water immediately following use.

If this product is mixed with pesticides, the entire mixture, including rinsate, must be handled and disposed of according to all applicable local, state, and federal guidelines.

Equipment Notice: Becker Underwood recommends the use of Teflon seals to aid in the prevention of leaks when using Green Lawngr in centrifugal pumps. Standard ceramic seals may leak during operation.

Caution

Keep out of the reach of children. Do not take internally. In case of eye contact, flush with large amounts of water and consult a physician. In case of ingestion, dilute with water or milk and consult a physician. Do not re-use this

container. Rinse contents into the spray tank and crush prior to disposal. Do not apply to food or feed crops or grain after harvest. A spray shield is recommended for applications if overspray or drift is a potential problem.
EMERGENCY CONTACT: CHEMTREC 1-800-424-9300

Notice: There are no warranties which extend beyond the description on the label hereof. The manufacturer, Becker Underwood, Inc., warrants this product to be as described on the label. The manufacturer's liability on this warranty is limited to return of the purchase price of this product. The buyer assumes all risks and liability resulting from the use of this product, whether used singly or in combination with other goods. The manufacturer neither assumes nor authorizes any person to assume for it any other liability in connection with the sale or use of this product.

Green Lawngr is a registered trademark of Becker Underwood, Inc.

manufactured by:

Becker Underwood, Inc.

801 Dayton Avenue
Ames, IA 50010
515-232-5907
Fax 515-232-5961
www.bucolour.com